

# JUAL HT [HANDY TALKY] - RADIO RIG / REAPETER - SEWA HT HARGA DAN SPESIFIKASI

*Washupito's Tiendita*

## JUAL RADIO RIG ICOM



### RADIO RIG ICOM [IC 2300 VHF]

RADIO RIG ICOM IC 2300 Powerful, Smaller and Simple to Use. A Great Update to the IC-2200H! Read the QST Review of the IC-2300H here! \*Click the image below to view the PDF review QST Review of the 2300H Icom introduces the new IC-2300H, 14 [\[Product Details...\]](#)

### RADIO RIG ICOM [M 304 MARINE]

RADIO RIG MARINE M 304 ICOM IC-M304 VHF Marine Mobile Transceiver \$ 172.00 Sorry... This Item is Out of Stock! ICOM IC-M304 VHF Marine Mobile Transceiver ICOM IC-M304 VHF Marine Mobile Transceiver It's not just another marine radio. Fully f [\[Product Details...\]](#)

### RADIO SSB ICOM [IC 710]

Features : Type:Amateur HF transceiver Frequency range:10-160 m Mode:SSB/CW/RTTY RF Power output:Max 100 W Sensitivity: N/A Selectivity: N/A Image rejection:N/A Voltage:13.8 VDC Current drain:RX: ? A TX: Max ? A Impedance:50 ohms, SO-239 [\[Product Details...\]](#)

### RADIO SSB MARINE [ICOM M 710]

Simple, dependable worldwide communications at an affordable price. The latest in Icom SSB technology and construction 150 watts of power, 100% duty cycle All modes, including RTTY E-mail ready for SeaWave. Optional filter required for Globe Wireles [\[Product Details...\]](#)

## RIG ICOM [IC 2820H DUAL BAND]

Specification Frequency coverage Version Transmit Receive (Unit: MHz) USA 144-148, (L):  
118-549.995 430-450\*1 (R): 118-173.995, 375-549.995, 810-999.99\*3 Australia 144-148,(L):  
118-549.995 430 [\[Product Details...\]](#)

## RIG ICOM [IC M412]

The built-in Class D DSC provides additional safety at sea. The built-in DSC watch function monitors Ch 70 (DSC channel) activity, even while you are receiving another channel. Distress, individual, group, all ships, position request/reply, polling request [\[Product Details...\]](#)

## RIG ICOM [IC M504 VHF]

Specification Frequency range Tx 156.025 - 157.425MHz Rx 156.050 - 163.275MHz Type of emission  
16K0G3E, 16K0G2B Usable channels USA, INT, CAN, WX channels Power supply requirement 13.8V DC  
±15% Current drain (at 13.8V DC) Transmitter [\[Product Details...\]](#)

## [IC 208H] VHF/UHF FM

Specification Version Guaranteed Tx Work Rx Work Range Range Range U.S.A. 144-148, 144-148,  
118-173.995, Frequency coverage 440-450 420-450 230-549.995, [\[Product Details...\]](#)

## [ID 800H] VHF/UHF DIGITAL

[\[Product Details...\]](#)

- « « Start
- « Prev
- 1
- Next »
- End » »
- 

Results 1 - 9 of 9